

# ONWARD BOUND

## 2B58

### Specification

<b>Product Type:</b>	Modular
<b>Construction:</b>	Tufted
<b>Surface Appearance:</b>	Textured Patterned Loop
<b>Gauge:</b>	1/12" (47.00 rows per 10 cm)
<b>Pile Weight:</b>	15 oz/yd <sup>2</sup> (509 g/m <sup>2</sup> )
<b>Pile Thickness:</b>	.105" (2.67 mm)
<b>Stitches Per Inch:</b>	12.2 (48.03 per 10 cm)
<b>Dye Method:</b>	100% Solution Dyed
<b>Fiber Type:</b>	Colorstrand® SD Nylon
<b>Stain Release Technology:</b>	Sentry Plus Stain Protection
<b>Soil Release Technology:</b>	Sentry Soil Protection
<b>Density:</b>	5,074
<b>Weight Density:</b>	75,095
<b>Primary Backing:</b>	Non-Woven Synthetic
<b>Secondary Backing:</b>	UltraSet with Recycled Content
<b>Installation Method:</b>	Quarter Turn / Monolithic / Vertical Ashlar / Brick Ashlar / Multi Directional
<b>Size:</b>	24' x 24" (.6096 m x .6096 m)
<b>Flammability:</b>	ASTM E 648 Class I (Glue Down)
<b>Smoke Density:</b>	ASTM E 662 Less than 450
<b>Static Propensity:</b>	AATCC-134 Under 3.5 KV
<b>IAQ Green Label Plus:</b>	1098
<b>CRI Appearance Retention Rating:</b>	Heavy Traffic
<b>Warranties:</b>	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty 10 Year Limited Stain Resistance Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants