

Pattern Perspective 2B176

PRODUCT TYPE:	Carpet Tile
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Textured Patterned Loop
GAUGE:	1/12" (47.00 rows per 10 cm)
PILE WEIGHT:	15 oz/yd ² (509 g/m ²)
PILE THICKNESS:	.074" (1.87 mm)
STITCHES PER INCH:	11.0 (43.31 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Colorstrand® SD Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	7,297
WEIGHT DENSITY:	109,459
PRIMARY BACKING:	Non-Woven Synthetic
SECONDARY BACKING:	UltraSet® Matrix
INSTALLATION METHOD:	Vertical Ashlar / Quarter Turn
SIZE:	24" x 24" (.6096 m x .6096 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	1171
CRI APPEARANCE RETENTION RATING:	Heavy Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light 10-Year Limited Stain Resistance Warranty 10-Year Limited Colorfastness to Atmospheric Contaminants