

# SET IN MOTION TILE 1T43

## PRODUCT SPECIFICATIONS

<b>PRODUCT TYPE:</b>	Carpet Tile
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Patterned Loop
<b>GAUGE:</b>	1/12" (47.00 rows per 10 cm)
<b>TUFTED WEIGHT:</b>	17 oz/yd <sup>2</sup> (576 g/m)
<b>PILE THICKNESS:</b>	.123" (3.12 mm)
<b>STITCHES PER INCH:</b>	9.2 (36.22 per 10 cm)
<b>DYE METHOD:</b>	100% Solution Dyed
<b>FIBER TYPE:</b>	Colorstrand® SD Nylon
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	4,976
<b>WEIGHT DENSITY:</b>	84,592
<b>PRIMARY BACKING:</b>	Non-Woven Synthetic
<b>SECONDARY BACKING:</b>	UltraSet®
<b>RECYCLED CONTENT:</b>	Contains a minimum of 39% pre-consumer recycled content by total product weight
<b>NSF 140</b>	Gold
<b>INSTALLATION METHOD:</b>	Monolithic / Quarter Turn / Brick Ashlar / Vertical Ashlar / Multi Directional
<b>SIZE:</b>	24" x 24" (.6096 m x .6096 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class I (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	Certified 1098
<b>APPEARANCE RETENTION RATING (TARR):</b>	Heavy Traffic
<b>WARRANTIES:</b>	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

*All specifications are subject to normal manufacturing tolerances. 6/15*

*For additional technical information, please contact Technical Services at **800.833.6954**.*